



MITA circle 200/240/450

recessed with trim


EN Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; optional: blind cover to cover the cut-out available as an accessory (MITA circle 240/450); suitable for ceiling thickness of 2-25 mm; surface powder coated; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination (MITA circle 200); energy-efficient LEDs with very good colour rendering

IT Corpo illuminante circolare in alluminio pressofuso; forma estremamente sottile; apparecchio da incasso con bordo perimetrale; in opzione: copertura cieca per l'inserimento nel vano interno disponibile come accessorio (MITA circle 240/450); per soffitti di spessore 2-25 mm; verniciatura a polvere; riflettore ad alta lucentezza con design sfaccettato; diffusore HPO (High Performance Opal) per un'illuminazione omogenea (MITA circle 200); LED ad efficienza energetica con elevata resa cromatica

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 80, 3 SDCM
 UGR ≤ 19 / 65° ≤ 1500 cd/m²
 up to 155 lm/W
 L95 @ 50 000 h
 DALI-2
 reflector (UGR ≤ 19), opal

Types



Colours




Light distribution



suitable for plasterboard or grid ceilings



DIN EN 12464-1
 UGR ≤ 19



tunable white
 2700-6500 K

Order options

COLOUR TEMPERATURE	☑☑
3000K	5
4000K	6
tunable white 2700–6500K*	D

*DALI-2 DT8

CONTROL

DALI-2

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

REFLECTOR COLOUR

chrome reflector	R
dark chrome reflector	B

LIGHT OPTIC COVER

reflector (UGR ≤ 19)
opal

Options on request

COLOUR RENDERING INDEX


CRI ≥ 90

GRID CEILING MOUNTING

installed in module 600 × 600 mm
installed in module 625 × 625 mm

INLAY

sensor
emergency light



MITA circle 200 trim




OPAL DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
17.5 W	3000K	1760 lm	074-812333☑☑☑
	4000K	1830 lm	
21.8 W	2700–6500K	1960 lm	074-8123D3☑☑

REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.5 W	3000K	1800 lm	074-812333☑☑☑
	4000K	1870 lm	
15.8 W	2700–6500K	1900 lm	074-8123D3☑☑



MITA circle 240 trim



REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.9 W	3000K	1950 lm	074-811433☑☑☑
	4000K	2160 lm	

MITA circle 450 trim



REFLECTOR DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000K	4220 lm	074-811633☑☑☑
	4000K	4650 lm	
41 W*	3000K	5490 lm	074-812633☑☑☑
	4000K	6060 lm	


*not for tunable white

Accessories

BLIND COVER

TYPE	ORDER CODE
MITA 240 circle recessed	074-891141☑
MITA 450 circle recessed	074-891161☑

Light distribution



reflector (UGR ≤ 19)
direct

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, reflector chrome