

## NOBA

suspended


**EN** Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

**DE** Dekorative Pendelleuchte aus Aluminium; Oberfläche chrom poliert, Aluminium gebürstet oder pulverbeschichtet; abgependelt mit Pendelabhangung, inkl. Einspeiseleitung (schwarz oder wei); beliebig kurzbar; hochwertige plano-konvexe Glaslinse; keine Mehrfachschatten; energieeffiziente LEDs mit sehr guter Farbwiedergabe; Baldachin fur Weiterverdrahtung; Konverter im Baldachin enthalten; Deckenmontageringe fur multiple Positionierung der Leuchte im Raum als Zubehor erhaltlich

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI ≥ 90  
up to 149 lm/W  
L90 @ 50 000 h  
non DIM, DALI-2, Casambi

### Types




### Canopy colours



### Luminaire colours



### Light distribution



free positioning by  
cable and hook



high quality  
glass lens

## Order options

### COLOUR TEMPERATURE

2700 K	9
3000 K	0
4000 K	1

### CONTROL

non DIM	1
DALI-2	3
Casambi	9

### MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

### CABLE COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8


### MATERIAL COLOUR CANOPY/ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

### BEAM ANGLE


wide flood 67°

## NOBA suspended




### NOBA 40 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	605lm	0 49-53 10 1 1 1 1 1 1
	3000 K	629lm	
	4000 K	659lm	



### NOBA 50 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	642lm	0 49-53 13 1 1 1 1 1 1
	3000 K	667lm	
	4000 K	699lm	



### NOBA 60 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	656lm	0 49-53 16 1 1 1 1 1 1
	3000 K	682lm	
	4000 K	715lm	



### CANOPY CEILING 220-240V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
150 mA   non DIM	η 79 %	115-29	0 05-26 0 1 2 1 1
150 mA   DALI-2	η 81 %	115-29	0 05-26 0 1 2 3 1
150 mA   Casambi	η 85 %	115-29	0 05-26 0 1 2 9 1



### MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 05-35 2 1 1 1 1



### MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9-25 mm

TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 05-35 1 1 1 1 1 7



### SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 63-89 1 2 1 1 0

necessary to install mounting set trimless

## Mounting accessories



### HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	0 30-10 0 0 0 1 1

## Electrical accessories

### POWER SUPPLY 220-240 V AC, 50-60 Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
150 mA   non DIM	η 80 %	93-36-25	0 02-90 8 1 0
150 mA   DALI-2	η 80 %	112-29-21	0 02-90 8 1 1
150 mA   Casambi*		95-37-20	0 02-90 8 1 2

\*DALI-2 power supply needed

### DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W   48V DC constant voltage	72-90-63	0 05-65 2 0 2 1 0
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2 × 42W   48V DC   U <sub>OUT</sub> 10-40V	36-88-59	0 05-61 2 1 0 3 0

**INSET POWER** is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour white