

VITA

wall

EN Luminaire housing, mounting channel and front cover from extruded aluminium profile, angular version; extremely slim luminaire housing (only 25 mm), for direct/indirect radiation characteristic; no visible screws; surface anodised; suitable for wall mounting; lighting modules with specially computed, asymmetrical high gloss reflectors, linear prismatic covers incl. foil with different light distributions for optimised light control and homogeneous illumination; lighting modules in aluminium, powder coated; CRI ≥ 90 or XPECTRUM; incl. 2 converters for separate control of the direct/indirect light component; energy-efficient LEDs with very good colour rendering

IT Corpo illuminante, canale di montaggio e copertura frontale in profilo di alluminio estruso, modello squadrato; corpo dell'apparecchio estremamente sottile (solo 25 mm), per un fascio di luce diretto/indiretto; nessuna vite visibile; superficie anodizzata; montaggio a parete; inserti luminosi con riflettori asimmetrici lucidi appositamente calcolati, cover prismatiche lineari incl. pellicola con diversa distribuzione della luce per la componente diretta o indiretta della luce, per un controllo della luce ottimizzato e un'illuminazione omogenea; inserti luminosi in alluminio verniciato a polvere; CRI ≥ 90 o XPECTRUM; incl. 2 convertitori per il controllo separato della componente della luce diretta/indiretta; LED ad efficienza energetica con elevata resa cromatica

Quickinfo


3000 K, 4000 K
CRI ≥ 90 , CRI ≥ 97 XPECTRUM
up to 121 lm/W
L80/85 @ 50 000 h
DALI-2
linear prismatic

Types

horizontal mounting





vertical mounting




Colour



Light distributions



system
solution



CRI ≥ 97
XPECTRUM

Order options

| | |
|----------------------------|----|
| COLOUR TEMPERATURE | ☑☑ |
| 3000 K (CRI ≥ 90) | 0 |
| 4000 K (CRI ≥ 90) | 1 |
| 3000 K (CRI ≥ 97 XPECTRUM) | Y |
| 4000 K (CRI ≥ 97 XPECTRUM) | Z |

CONTROL

DALI-2

direct/indirect separately controllable

MATERIAL COLOUR

● anodised aluminium

LIGHT INSET COVER

linear prismatic

Options on request

COLOUR TEMPERATURE


tunable white (2700–6500 K)

MATERIAL COLOUR

white, black, special colours

SPOTLIGHT ALIGNMENT

SPOTLIGHT for reading




VITA wall



DIRECT/INDIRECT - HORIZONTAL MOUNTING


| SYS. POWER | LUMINOUS FLUX | L (mm) | ORDER CODE |
|------------|--------------------|--------|---------------|
| 123 W | ↓ 7460 / ↑ 7460 lm | 1013 | 099-9136☑☑36A |
| 158 W | ↓ 8950 / ↑ 8950 lm | 1213 | 099-9137☑☑36A |



DIRECT/INDIRECT - VERTICAL MOUNTING

| SYS. POWER | LUMINOUS FLUX | L (mm) | ORDER CODE |
|------------|--------------------|--------|---------------|
| 123 W | ↓ 7460 / ↑ 7460 lm | 1013 | 099-9166☑☑36A |
| 158 W | ↓ 8950 / ↑ 8950 lm | 1213 | 099-9167☑☑36A |

Light distribution



asymmetric linear prismatic
direct/indirect

LUMINOUS FLUX value calculated for

4000 K, CRI ≥ 90, white;
3000 K CRI90-9%, 3000 K CRI97 -24%,
4000 K CRI97 -22%