



Allgemein

Decke, Track

schwenkbar max. 310°

Rotierbarkeit 360°

Weiß, RAL 9016¹

IP20

686²-1170³ lm

LED

3000 K

CRI ≥ 95

L90 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99, R_f: 94, R₍₁₋₁₅₎: 96

MR 0.66

MDER 0.6

Optisch

focus

Ausstrahlwinkel 17°²-47°³

PstLM ≤ 1.0^{2 3 4}

SVM ≤ 0.4^{2 3 4}

Elektrisch

DALI-2

220-240 V

System 23.0 W

System 30²-51³ lm/W⁵

SK1

1 DALI Addr.

Abmessungen


Durchmesser 70 mm

Höhe 106 mm

0.9 kg


werkzeuglose Montage

Lichtverteilung



focus 47°


h (m)	E0° (lx)	ø (m)
1	2020	0.87
2	510	1.74
3	220	2.60
4	130	3.47
5	80	4.34



focus 17°

h (m)	E0° (lx)	ø (m)
1	4900	0.30
2	1220	0.60
3	540	0.89
4	310	1.19
5	200	1.49

Produktskizze



¹ RAL Code ² kleinster Ausstrahlwinkel ³ größter Ausstrahlwinkel

⁴ Wert von umgebendem Produkt bei Vollast (ungedimmt)

⁵ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Montageanleitung



Beleuchtungsrechner

