



Allgemein

Decke, Track

schwenkbar max. 310°

Rotierbarkeit 360°

Weiß, RAL9016¹

IP20

754²-1280³ lm

LED

4000 K

CRI ≥ 95

L90 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 98, R_f: 91, R₍₁₋₁₅₎: 95

MR 0.85

MDER 0.77

Optisch

focus

Ausstrahlwinkel 17°²-47°³

PstLM ≤ 1.0⁴

SVM ≤ 0.4⁴

Elektrisch

DALI-2

220-240 V

System 23.0 W

SK1

System 33²-56³ lm/W⁵

1 DALI Addr.

Abmessungen


Durchmesser 70 mm

Höhe 106 mm

0.9 kg


Feststellschraube (Werkzeug erforderlich)

Lichtverteilung



focus 47°


h (m)	E0° (lx)	ø (m)
1	2210	0.87
2	550	1.74
3	250	2.60
4	140	3.47
5	90	4.34



focus 17°

h (m)	E0° (lx)	ø (m)
1	5380	0.30
2	1350	0.60
3	600	0.89
4	340	1.19
5	220	1.49

Produktskizze



¹ RAL Code ² kleinster Ausstrahlwinkel ³ größter Ausstrahlwinkel

⁴ Wert von umgebendem Produkt bei Vollast (ungedimmt)

⁵ inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

Montageanleitung



Beleuchtungsrechner

