



## Allgemein

Decke, Track

Schwenkbar max. 310°

Rotierbarkeit 360°

Schwarz, RAL 9005 <sup>1</sup>

IP20

1000 lm

## LED

4000 K

CRI ≥ 95

L90 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 98, R<sub>f</sub>: 91, R<sub>(1-15)</sub>: 95

MR 0.85

MDER 0.77

## Optisch

flood

Ausstrahlwinkel 39°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DIM POTI

220-240 V

System 13.9 W

System 72 lm/W<sup>3</sup>

SK1

## Abmessungen


Durchmesser 70 mm

Höhe 98 mm

0.9 kg

werkzeuglose Montage


## Lichtverteilung



flood 39°

h (m)	EO° (lx)	ø (m)
1	2010	0.70
2	500	1.41
3	220	2.11
4	130	2.82
5	80	3.52

## Produktskizze



<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Montageanleitung



## Beleuchtungsrechner

