



## Allgemein

Decke , Track

schwenkbar max. 310°

Rotierbarkeit 360°

Schwarz , RAL 9005 <sup>1</sup>

IP20

900 lm

## LED

3000 K

CRI ≥ 95

L90 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 94 , R<sub>(1-15)</sub>: 96

MR 0.66

MDER 0.6

## Optisch

wide flood

Ausstrahlwinkel 58°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DIM POTI

220-240 V

System 13.9 W

System 65 lm/W<sup>3</sup>

SK1

## Abmessungen


Durchmesser 70 mm

Höhe 98 mm

0.9 kg

werkzeuglose Montage


## Lichtverteilung



wide flood 58°

h (m)	EO° (lx)	ø (m)
1	1130	1.12
2	280	2.24
3	130	3.35
4	70	4.47
5	50	5.59

## Produktskizze



<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts

## Montageanleitung



## Beleuchtungsrechner

