

UNICO

wall recessed

EN Recessed wall luminaire in aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; installation possible in different housings; surface powder coated; incl. external converter; high-quality reflector with micro-faceted, aluminum-vaporised surface; different asymmetrical light distributions; installation optionally for floor or ceiling illumination; energy-efficient high power LEDs with very good colour rendering

DE Wandeinbauleuchte aus Aluminium; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Einbau in unterschiedlichen Gehäusen möglich; Oberfläche pulverbeschichtet; inkl. externem Konverter; hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; unterschiedliche asymmetrische Lichtverteilungen; Montage wahlweise zur Boden- oder Deckenaufhellung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 62lm/W
 L90 @ 50 000h
 non DIM, DALI-2

Types



Colours



Light distribution



homogeneous floor illumination



safety glass for dust protection



tunable white 2700–5000K

Order options

COLOUR TEMPERATURE

| | |
|--------|---|
| 2700 K | 4 |
| 3000 K | 5 |
| 4000 K | 6 |

CONTROL

| | |
|---------|---|
| non DIM | 1 |
| DALI-2 | 3 |

LIGHT OPTIC

wide floor

MATERIAL COLOUR

| | |
|---|---|
| <input type="radio"/> traffic white RAL 9016 | W |
| <input checked="" type="radio"/> jet black RAL 9005 | B |

Options on request

COLOUR TEMPERATURE

tunable white 2700–5000K

only available for 2 lamps | DALI-2 DT8

UNICO wall recessed



1 LAMP

| | | |
|---------------------|----------------------|-------------------|
| SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
| 9.9 W | 562 lm | 090-6L1::UB001 |



2 LAMPS

| | | |
|---------------------|----------------------|-------------------|
| SYSTEM POWER | LUMINOUS FLUX | ORDER CODE |
| 17.3 W | 1070 lm | 090-6L2::UB001 |

Accessories

MOUNTING SET WITH TRIM

for intermediate ceilings 2–25 mm

| TYPE | L-W-H (mm) | CUTOUT (mm) | ORDER CODE |
|---------|------------|-------------|------------|
| 1 lamp | 101-63-20 | 90-50 | 090-7L2020 |
| 2 lamps | 101-101-30 | 90-90 | 090-7Q4020 |

TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm

| TYPE | L-W-H (mm) | CUTOUT (mm) | ORDER CODE |
|---------|------------|-------------|-------------|
| 1 lamp | 88-50-47 | 90-50 | 090-7L20100 |
| 2 lamps | 85-85-47 | 90-90 | 090-7Q40100 |

PRIMED CONCRETE MOUNTING SET

| TYPE | L-W-H (mm) | ORDER CODE |
|--------------------------|-------------|-------------|
| primed concrete ceilings | 240-400-130 | 052-1914320 |


order mounting set separately

Planning information

wide floor



Light distribution



microprismatic
direct/indirect power

LUMINOUS FLUX value calculated for
3000 K, CRI ≥ 90, colour white, reflector chrome
2700 K -6%, 4000 K +7%