

# UNICO L2 basic

ceiling

090-1L243RG001



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

Grau , RAL 9006 <sup>1</sup>

Reflektor Chrom

IP20

912 lm

## LED

2700 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 101 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 89

MR 0.56

MDER 0.51

## Optisch

rectangular medium

Ausstrahlwinkel 34°x69°

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

220-240 V

System 12.6 W

System 72 lm/W<sup>3</sup>

SK1

## Abmessungen

Länge 88 mm

Breite 51 mm

Höhe 90 mm

0.35 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

