

TASK angular direct / indirect power

suspended

059-5283137K



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke , Abgehängt

Weiß , RAL 9010 ¹

IP20

indirekt 8050 lm

direkt 15500 lm

gesamt 23600 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.75

MDER 0.68

Optisch

Microprismatic

microprismatic

UGR ≤ 19 , $\geq 65^\circ$ < 3000 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Elektrisch

DALI-2

220-240 V

System 197 W

System 120 lm/W³

SK1

8 DALI Addr.

Abmessungen

Kabel 1500 mm

Länge 1535 mm

Breite 1535 mm

Höhe 36 mm

18.9 kg

¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



Produktskizze

