

TASK 900 round direct / indirect power

suspended

059-0463138K



Projekt / Typ

Notizen

Anzahl / Datum



IP 40



Allgemein

Decke , Abgehängt

Schwarz , RAL 9005 ¹

IP40

indirekt 4370 lm

direkt 9370 lm

gesamt 13740 lm

LED

4000 K

CRI \geq 90

L90 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.75

MDER 0.68

Optisch

Microprismatic

microprismatic

UGR \leq 19 , $\geq 65^\circ$ <3000 cd/m²

P_{stLM} \leq 1.0 ²

SVM \leq 0.4 ²

Elektrisch

DALI-2

220-240 V

System 100 W

System 137 lm/W³

SK1

2 DALI Addr.

Abmessungen

Pende 1000 mm

Durchmesser 900 mm

Höhe 41 mm


14 kg

¹ RAL Code


² Wert von umgebendem Produkt bei Vollast (ungedimmt)

³ inkl. Berücksichtigung von optischen, internen Steuergeräteverlusten & der Effizienz des Betriebsgeräts

Lichtverteilung



Produktskizze



Montageanleitung



Beleuchtungsrechner

