

# SASSO 100 round adjustable

ceiling

048-34105311S



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

schwenkbar max. 20°

Rotierbarkeit 360°

Schwarz , RAL9005/black <sup>1</sup>

Reflektor Schwarz

IP20

1410 lm

## LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-5)</sub>: 88

MR 0.59

MDER 0.53

## Optisch

spot

Ausstrahlwinkel 19°

UGR < 13 , ≥ 65° < 3000 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DALI-2

20.2 W

SK1 220-240V

70 lm/W

1 DALI Addr.

## Abmessungen

Durchmesser 100 mm


Höhe 162 mm

0.95 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

## Lichtverteilung



## Produktskizze

