

# SASSO 100 square adjustable

ceiling

048-33104317W



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

schwenkbar max. 20°

Schwarz , RAL9005/white <sup>1</sup>

Innenfarbe Weiß

IP20

1620 lm

## LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.53

MDER 0.48

## Optisch

wide flood

Ausstrahlwinkel 58°

UGR < 19 , ≥65° <3000 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DALI-2

220-240 V

System 20.2 W

SK1

System 80 lm/W<sup>3</sup>

1 DALI Addr.

## Abmessungen

Länge 100 mm

Breite 100 mm

Höhe 162 mm


1.1 kg

<sup>1</sup> RAL Code


<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

## Lichtverteilung



## Produktskizze



## Montageanleitung



## Beleuchtungsrechner

