

SASSO 100 square downlight

trim

048-2710619M 048-279731G 002-90776



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Einbau

Gold, RAL260-M¹

Montage Set Silber-grau

Vorderseite IP44, Rückseite IP20

2080 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97, R_r: 90, R_{t(1-15)}: 89

MR 0.81

MDER 0.74

Optisch

medium

Ausstrahlwinkel 33°x34°

UGR < 16 , $\geq 65^\circ < 3000$ cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Elektrisch

DALI-2

29.2 W

Einsatz 24.8 W

36 Vf

700 mA

SK2 220-240V

71 lm/W

1 DALI Addr.

Abmessungen

mit Rand

Länge 118 mm

Breite 118 mm

Höhe 75 mm

0.53 kg

Ausschnitt

Länge 112 mm

Breite 112 mm

min. Deckenstärke 2 mm

max. Deckenstärke 25 mm

Einbautiefe 80 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Volllast (ungedimmt)


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



Produktskizze

