

# SASSO 100 square downlight

trimless

048-2710619M 048-2797117 002-90776



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke, Einbau

Gold, RAL260-M<sup>1</sup>

Montage Set Verkehrsweiß

Vorderseite IP44, Rückseite IP20

2080 lm

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97, R<sub>f</sub>: 90, R<sub>t(1-15)</sub>: 89

MR 0.81

MDER 0.74

## Optisch

medium

Ausstrahlwinkel 33°x34°

UGR < 16, ≥ 65° < 3000 cd/m<sup>2</sup>

PstLM ≤ 1.0<sup>2</sup>

SVM ≤ 0.4<sup>2</sup>

## Elektrisch

DALI-2

29.2 W

Einsatz 24.8 W

36 V

700 mA

SK2 220-240V

71 lm/W

1 DALI Addr.

## Abmessungen

randlos

Länge 105 mm

Breite 105 mm

Höhe 75 mm

0.51 kg

## Ausschnitt

Länge 106 mm

Breite 106 mm

min. Deckenstärke 12.5 mm

max. Deckenstärke 25 mm

Einbautiefe 80 mm

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

