

SASSO PRO 100

adjustable offset trim square

048-2411E37F 052-1952418



Projekt / Typ	
Notizen	
Anzahl / Datum	



Allgemein

Decke , Einbau
schwenkbar max. 35°
Rotierbarkeit 360°
Weiß , RAL9016 ¹
Montage Set Tiefschwarz
IP20
853 lm

LED

colour warm dimming
2000 K - 3000 K
CRI ≥ 95
L80 / 50000 h
initial MacAdam ≤ 4 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 90
MR 0.61
MDER 0.55

Optisch

flood
beam angle 36°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Elektrisch

DALI-2
14.9 W
SK2 220-240V
57 lm/W
Einsatz 68 lm/W
1 DALI Addr.

Abmessungen

mit Rand
length 112 mm
width 112 mm
Höhe 106 mm
0.59 kg


Ausschnitt

diameter 108 mm
min. ceiling thickness 5 mm
max. ceiling thickness 25 mm
recessed depth 130 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)



Lichtverteilung



flood 36°

h (m)	E0° (lx)	ø (m)
1	2120	0.65
2	530	1.31
3	240	1.96
4	130	2.61
5	80	3.27

Produktskizze



Montageanleitung



Beleuchtungsrechner

