



## Allgemein

Decke , Track

schwenkbar max. 310°

Rotierbarkeit 360°

Weiß , RAL9016 <sup>1</sup>

IP20

890<sup>2</sup>, 911<sup>3</sup>, 961<sup>4</sup>, 981<sup>5</sup>, 1010<sup>6</sup>, 1010<sup>7</sup> lm

## LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 98 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.6

MDER 0.55

## Optisch

wide flood<sup>2</sup>, medium<sup>3</sup>, flood<sup>4</sup>, flood<sup>5</sup>, spot<sup>6</sup>, super spot<sup>7</sup>

Ausstrahlwinkel 64°<sup>2</sup>, 30°<sup>3</sup>, 38°<sup>4</sup>, 40°<sup>5</sup>, 19°<sup>6</sup>, 10°<sup>7</sup>

PstLM ≤ 1.0 <sup>8</sup>

SVM ≤ 0.4 <sup>8</sup>

## Elektrisch

DIM POTI

220-240 V

System 14.7 W

SK1

System 61<sup>2</sup>, 62<sup>3</sup>, 65<sup>4</sup>, 67<sup>5</sup>, 69<sup>6</sup>, 69<sup>7</sup> lm/W<sup>9</sup>

## Abmessungen

Durchmesser 70 mm

Höhe 98 mm

0.92 kg

werkzeuglose Montage

<sup>1</sup> RAL Code <sup>2</sup> 64 Grad <sup>3</sup> 30 Grad <sup>4</sup> 38 Grad <sup>5</sup> 40 Grad <sup>6</sup> 19 Grad <sup>7</sup> 10 Grad

<sup>8</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>9</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

## Montage- anleitung



## Beleuchtungs- rechner





Lichtverteilung



super spot 10°

h (m)	E0° (lx)	ø (m)
1	23700	0.18
2	5900	0.36
3	2600	0.53
4	1500	0.71
5	900	0.89

spot 19°

h (m)	E0° (lx)	ø (m)
1	6160	0.33
2	1540	0.65
3	680	0.98
4	390	1.31
5	250	1.63

medium 30°

h (m)	E0° (lx)	ø (m)
1	2070	0.54
2	520	1.08
3	230	1.63
4	130	2.17
5	80	2.71

flood 38°

h (m)	E0° (lx)	ø (m)
1	1710	0.69
2	430	1.37
3	190	2.06
4	110	2.75
5	70	3.43

flood 40°

h (m)	E0° (lx)	ø (m)
1	1750	0.72
2	440	1.44
3	190	2.16
4	110	2.88
5	70	3.60

wide flood 64°

h (m)	E0° (lx)	ø (m)
1	735	1.24
2	184	2.48
3	82	3.72
4	46	4.96
5	29	6.19

Produktskizze

