



Allgemein

Decke, Track

schwenkbar max. 310°

Rotierbarkeit 360°

Weiß, RAL9016¹

IP20

957², 979³, 1030⁴, 1050⁵, 1090⁶, 1090⁷ lm

LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 94, R_f: 87, R_{f(1-15)}: 90

MR 0.86

MDER 0.78

Optisch

wide flood², medium³, flood⁴, flood⁵, super spot⁶, spot⁷

Ausstrahlwinkel 64°², 30°³, 38°⁴, 40°⁵, 10°⁶, 19°⁷

PstLM ≤ 1.0⁸

SVM ≤ 0.4⁸

Elektrisch

DIM POT1

14.7 W

SK1 220-240V

65², 67³, 70⁴, 71⁵, 74⁶, 74⁷ lm/W⁹

Einsatz 77², 78³, 83⁴, 84⁵, 87⁶, 87⁷ lm/W¹⁰

Abmessungen

Durchmesser 70 mm

Höhe 98 mm

0.92 kg

Feststellschraube (Werkzeug erforderlich)

¹ RAL Code ² 64 Grad ³ 30 Grad ⁴ 38 Grad ⁵ 40 Grad ⁶ 10 Grad ⁷ 19 Grad

⁸ Wert von umgebendem Produkt bei Vollast (ungedimmt)

⁹ inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

¹⁰ inkl. Berücksichtigung von optischen Verlusten

Montage-anleitung



Beleuchtungs-rechner





Lichtverteilung



super spot 10°

h (m)	E0° (lx)	ø (m)
1	25600	0.18
2	6400	0.36
3	2800	0.53
4	1600	0.71
5	1000	0.89

spot 19°

h (m)	E0° (lx)	ø (m)
1	6650	0.33
2	1660	0.65
3	740	0.98
4	420	1.31
5	270	1.63

medium 30°

h (m)	E0° (lx)	ø (m)
1	2220	0.54
2	560	1.08
3	250	1.63
4	140	2.17
5	90	2.71

flood 38°

h (m)	E0° (lx)	ø (m)
1	1830	0.69
2	460	1.37
3	200	2.06
4	110	2.75
5	70	3.43

flood 40°

h (m)	E0° (lx)	ø (m)
1	1870	0.72
2	470	1.44
3	210	2.16
4	120	2.88
5	70	3.60

wide flood 64°

h (m)	E0° (lx)	ø (m)
1	790	1.24
2	198	2.48
3	88	3.72
4	49	4.96
5	32	6.19

Produktskizze

