

# SETA 60 CONEX reflector

## direct / indirect socket / socket

suspended system

058-4138538R



Projekt / Typ

Notizen

Anzahl / Datum



### Allgemein

Decke , Abgehängt

Schwarz , RAL9005 <sup>1</sup>

Chrom

IP20

indirekt 6510 lm

direkt 6170 lm

gesamt 12680 lm

### LED

3000 K

CRI  $\geq$  80

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

MR 0.56

MDER 0.51

### Optisch

Reflector

symmetric

UGR  $< 13$  ,  $\geq 65^\circ$   $< 1500$  cd/m<sup>2</sup>

PstLM  $\leq 1.0$  <sup>2</sup>

SVM  $\leq 0.4$  <sup>2</sup>

### Elektrisch

DALI-2

System 87 W

SK1 220-240V

System 146 lm/W<sup>3</sup>

2 DALI Addr.

### Abmessungen

Länge 2351 mm

Breite 60 mm


Höhe 60 mm

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

### Lichtverteilung



### Produktskizze



### Montage- anleitung



### Beleuchtungs- rechner

