

## 030-6530634M



Anzahl / Datum



Decke / Wand , Track
schwenkbar max. 135°
Rotierbarkeit 365°
Chrom
IP20
359 lm
Optischer Einsatz 70 lm/W <sup>1</sup>

4000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>f[1-15]</sub> : 89
MR 0.81
MDER 0.74

medium
Ausstrahlwinkel 26°
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

DALI-2
48 V
Einsatz 5.7 W
Optischer Einsatz 5.1 W
SK3
1 DALI Addr.

Durchmesser 22 mm  
Höhe 100 mm

h (m)	E0° (lx)	ø (m)
1	1740	0.46
2	440	0.92
3	190	1.37
4	110	1.83
5	70	2.29

# TILA 22 adjustable

MOVE IT 10  
030-6530634M



Projekt / Typ

Notizen

Anzahl / Datum

## Montagezubehör

### HOOK

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Verkehrsweiß	16	030-1000017
Tiefschwarz	16	030-1000018



## Optisches Zubehör

### HONEYCOMB LOUVER

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Tiefschwarz	20	007-1965118

