

## 030-6530439M



Projekt / Typ

## Notizen

Anzahl / Datum



Decke / Wand , Track
schwenkbar max. 135°
Rotierbarkeit 365°
Roségold
IP20
324 lm
Optischer Einsatz 63 lm/W <sup>1</sup>

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99, R <sub>f</sub> : 91, R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

medium
Ausstrahlwinkel 26°
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

DALI-2
48 V
Einsatz 5.7 W
Optischer Einsatz 5.1 W
SK3
1 DALI Addr.

Durchmesser 22 mm  
Höhe 100 mm

h (m)	E0° (lx)	ø (m)
1	1570	0.46
2	390	0.92
3	170	1.37
4	100	1.83
5	60	2.29

<sup>1</sup> inkl. Berücksichtigung von optischen Verlusten

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

# TILA 22 adjustable

MOVE IT 10  
030-6530439M



Projekt / Typ

Notizen

Anzahl / Datum

## Montagezubehör

### HOOK

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Verkehrsweiß	16	030-1000017
Tiefschwarz	16	030-1000018



## Optisches Zubehör

### HONEYCOMB LOUVER

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Tiefschwarz	20	007-1965118

