

030-6530435M



Projekt / Typ

Notizen

Anzahl / Datum



Decke / Wand , Track
schwenkbar max. 135°
Rotierbarkeit 365°
gun metal
IP20
324 lm
Optischer Einsatz 63 lm/W ¹

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99, R _f : 91, R _{1-15} : 89
MR 0.53
MDER 0.48

medium
Ausstrahlwinkel 26°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

DALI-2
48 V
Einsatz 5.7 W
Optischer Einsatz 5.1 W
SK3
1 DALI Addr.

Durchmesser 22 mm
Höhe 100 mm

h (m)	E0° (lx)	ø (m)
1	1570	0.46
2	390	0.92
3	170	1.37
4	100	1.83
5	60	2.29

¹ inkl. Berücksichtigung von optischen Verlusten

² Wert von umgebendem Produkt bei Volllast (ungedimmt)

TILA 22 adjustable

MOVE IT 10
030-6530435M



Projekt / Typ

Notizen

Anzahl / Datum

Montagezubehör

HOOK

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Verkehrsweiß	16	030-1000017
Tiefschwarz	16	030-1000018



Optisches Zubehör

HONEYCOMB LOUVER

FARBE	Ø (MM)	ARTIKELNUMMER(N)
Tiefschwarz	20	007-1965118

