

BO 55

track
180-7312738S



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein
Decke , Track
schwenkbar max. 90°
Rotierbarkeit 355°
Schwarz , RAL9005 ¹
IP20
2120 lm


LED
3500 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₁₅₎ : 89
MR 0.7
MDER 0.63

Optisch
spot
Ausstrahlwinkel 17°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Elektrisch
DALI-2
System 24.7 W
SK2 220-240V
System 86 lm/W ³
1 DALI Addr.


Abmessungen
Durchmesser 55 mm
Höhe 140 mm
0.5 kg

Lichtverteilung



h (m)	EO ³ (lx)	ø (m)
1	14800	0.29
2	3700	0.58
3	1600	0.87
4	900	1.16
5	600	1.45

Produktskizze



¹ RAL Code
² Wert von umgebendem Produkt bei Vollast (ungedimmt)
³ inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

Montageanleitung



Beleuchtungsrechner

