

MOVE IN 45 square

trimless

063-8421417M 063-8832117 002-90728



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Halbeinbau

Weiß, RAL9016¹

IP20

1200 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99, R_f: 91, R₍₁₋₁₅₎: 89

MR 0.53

MDER 0.48

Optisch

medium

beam angle 24°

PstLM ≤ 1.0²

SVM ≤ 0.4²

Elektrisch

DALI-2

15.9 W

Einsatz 13.5 W

36 Vf

400 mA

SK2 220-240V

75 lm/W

1 DALI Addr.

Abmessungen

randlos

diameter 80 mm

Höhe 105 mm

0.31 kg

Ausschnitt

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 175 mm

¹ RAL Code

² Wert von umgebendem Produkt bei Vollast (ungedimmt)


Montage- anleitung



Beleuchtungs- rechner



Lichtverteilung



medium 24°

h (m)	E0° (lx)	ø (m)
1	5780	0.43
2	1440	0.86
3	640	1.30
4	360	1.73
5	230	2.16

Produktskizze

