

BO 45 semi-recessed

049-613041XV 002-90729



Projekt / Typ

Notizen

Anzahl / Datum



Allgemein

Decke, Halbeinbau

schwenkbar max. 90°

Rotierbarkeit 350°

Spezialfarben

IP20

346 lm

LED

2700 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99, R_f: 91, R₍₁₋₁₅₎: 89

MR 0.54

MDER 0.49

Optisch

super spot

beam angle 8°

PstLM ≤ 1.0¹

SVM ≤ 0.4¹

Elektrisch

DALI-2

9.3 W

Einsatz 6.9 W

11 Vf

600 mA

SK2 220-240V

37 lm/W

1 DALI Addr.

Abmessungen

diameter 45 mm

Höhe 149 mm

0.04 kg

Ausschnitt

diameter 46 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 150 mm

¹ Wert von umgebendem Produkt bei Vollast (ungedimmt)


Lichtverteilung



super spot 8°

h (m)	EO° (lx)	ø (m)
1	12100	0.14
2	3000	0.28
3	1300	0.41
4	800	0.55
5	500	0.69

Produktskizze



Montage- anleitung



Beleuchtungs- rechner

