

# MINO 40 mid lumen

surface

042-111213GZ



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

Grau , RAL 9006 <sup>1</sup>

IP20

1300 lm

1300 lm/m

## LED

4000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 92 , R<sub>t(1-15)</sub>: 90

MR 0.81

MDER 0.74

## Optisch

Microprismatic

microprismatic

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

220-240 V

System 12.1 W

System 107 lm/W<sup>3</sup>

SK1

12 W/m

## Abmessungen

Länge 1008 mm

Breite 40 mm

Höhe 65 mm

1.7 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen, internen

Steuergeräteverlusten & der Effizienz des Betriebsgeräts


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

