

# MINO 60 high lumen

ceiling / suspended system

007-93M4137 006-16122H 046-4004017



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Abgehängt

Weiß , RAL9010 <sup>1</sup>

2200 lm/m

IP20

2570 lm

## LED

4000 K

CRI ≥ 90

L90 / 50000 h

photobiologische Sicherheit RG 0 - kein Risiko

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 90

MR 0.81

MDER 0.74

## Optisch

High Performance Opal

opal (lambertsch)

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DALI-2

23.3 W

SK1 220-240V

110 lm/W

1 DALI Addr.

20 W/m

## Abmessungen

mit Rand

length 1172 mm

width 60 mm

Höhe 80 mm

2.87 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

