

# MINO 60 high lumen

ceiling / suspended system

007-9335D37 006-16152Z 046-400501G



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Abgehängt

Grau , RAL9006 <sup>1</sup>

2220 lm/m

IP20

3270 lm

## LED

tunable white

2700 K - 6500 K

CRI  $\geq$  80

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

MR 0.48

MDER 0.44

## Optisch

Microprismatic

microprismatic

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2 DT8

220-240 V

System 31 W

SK1

System 105 lm/W<sup>3</sup>

1 DALI Addr.

21 W/m

## Abmessungen

Länge 1472 mm

Breite 60 mm

Höhe 80 mm

3.8 kg

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

