

# TUBIN 60 CONEX socket / socket

surface / suspended system

058-5034038C



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke / Wand , Aufbau

Schwarz , RAL9005 <sup>1</sup>

2490 lm/m

IP20

2930 lm

## LED

3000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.61

MDER 0.55

## Optisch

Clear Cover

opal (lambertsch)

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Elektrisch

DALI-2

System 27.9 W

SK1 220-240V

System 105 lm/W<sup>3</sup>

24 W/m


## Abmessungen

Länge 1181 mm

Breite 60 mm

Höhe 60 mm

## Lichtverteilung



## Produktskizze



<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Volllast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts

## Montageanleitung

