

# MINO 40 reflector

surface

042-1116137B



Projekt / Typ

Notizen

Anzahl / Datum



## Allgemein

Decke , Aufbau

RAL Reinweiß , RAL 9010 <sup>1</sup>

Reflektor Dunkles Chrom

2370 lm/m

IP20

7090 lm

## LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 , R<sub>f</sub>: 92 , R<sub>(1-15)</sub>: 90

MR 0.81

MDER 0.74

## Optisch

Reflector

Symmetric

UGR < 19 , ≥65° <1500 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Elektrisch

DALI-2

220-240 V

System 67 W

SK1

System 106 lm/W<sup>3</sup>

22 W/m

## Abmessungen

Länge 3008 mm

Breite 40 mm

Höhe 65 mm

<sup>1</sup> RAL Code

<sup>2</sup> Wert von umgebendem Produkt bei Vollast (ungedimmt)

<sup>3</sup> inkl. Berücksichtigung von optischen Verlusten und der Effizienz des Betriebsgeräts


## Montage- anleitung



## Beleuchtungs- rechner



## Lichtverteilung



## Produktskizze

