

MINO 40 reflector

surface

042-1113137R



Projekt / Typ
Notizen
Anzahl / Datum



220-240V	X-PERT	UGR ≤ 19	cd/m ² ≤ 1500	CRI ≥ 90	X-PERT
----------	--------	----------	--------------------------	----------	--------

Allgemein

Decke , Aufbau
RAL Reinweiß , RAL 9010 ¹
Reflektor Chrom
3260 lm/m
IP20
4880 lm

LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90
MR 0.81
MDER 0.74

Optisch

Reflector
Symmetric
UGR < 19 , ≥ 65° < 1500 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Elektrisch


DALI-2
36 W
SK1 220-240V
136 lm/W
24 W/m

Abmessungen

length 1508 mm
width 40 mm
Höhe 65 mm

¹ RAL Code
² Wert von umgebendem Produkt bei Vollast (ungedimmt)

Lichtverteilung



Produktskizze



Montage-anleitung



Beleuchtungs-rechner

