



SASSO 100 round

recessed

EN Round recessed spotlight; installation without tools in mounting set (trimless or with trim) with ball catch system; surface lacquered; installation possible in different housings; choice of adjustable / fixed symmetric or asymmetric radiation characteristic; variants with symmetric radiation characteristic: precise radiation characteristic due to high quality lens system; variants with asymmetric radiation characteristic: high-quality reflector with micro-faceted, aluminum-vaporised surface; COB (Chip on Board) technology for maximum efficiency (ADJUSTABLE and DOWNLIGHT); no multiple shadows; efficient LEDs with very good colour rendering

DE Runder Einbaustrahler; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; Oberfläche lackiert; Einbau in unterschiedlichen Gehäusen möglich; wahlweise einstellbar / starr symmetrische oder asymmetrische Abstrahlcharakteristik; symmetrisch strahlende Varianten: präzise Abstrahlcharakteristik durch hochwertige Linsenoptik; asymmetrische strahlende Varianten: hochwertiger Reflektor mit mikrofacettierter, aluminiumbedampfter Oberfläche; COB (Chip on Board) Technologie für höchste Effizienz (ADJUSTABLE und DOWNLIGHT); keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K,
CWD 1800–3000 K
CRI ≥ 90, 2 SDCM
up to 122 lm/W
L80 @ 50000 h
non DIM, DALI-2
↓ IP44 / ↑ IP20

Types



Housing colours



Inset colours



Light distributions



rotatable 360°,
tiltable 30°



wallwasher and
ww floor inset



glare control
(UGR ≤ 16)



80 mm
recess depth



CWD
1800–3000 K



CRI ≥ 95
2 SDCM

Electrical accessories

SASSO 100

POWER SUPPLY 220-240 V AC, 50-60Hz, PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
450 mA non DIM	η 88 %	143-43-30	002-90766
450 mA DALI-2	η 88 %	143-43-30	002-90767
650 mA non DIM	η 88 %	143-43-30	002-90780
650 mA DALI-2	η 88 %	143-43-30	002-90789
700 mA non DIM	η 80 %	143-43-30	002-90774
700 mA DALI-2	η 88 %	143-43-30	002-90776

THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable \varnothing 4-12mm	105-58-30	005-2531110
DALI cable \varnothing 4-12mm	105-58-30	005-2551110

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC 160 W 48V DC constant voltage	72-90-63	005-6520210
LED DRIVER DALI-2 DT6 1-2 addr. 200-1050 mA settable const. current 2 × 42W 48V DC U _{OUT} 10-40V	36-88-59	005-6121030

for more details and components see catalog XAL 22, page 981