



048-2800614M 048-2898318 002-90753



Decke , Einbau
Rotierbarkeit 360°
Matt Silber
Tiefschwarz
Vorderseite IP44 , Rückseite IP20
800 lm


4000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 94 , R _f : 87 , R _{f[1:5]} : 90
MR 0.86
MDER 0.78

medium
Ausstrahlwinkel 25°
UGR < 10
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Elektrisch
DALI-2
220-240 V
System 12.0 W
Einsatz 5.1 W
12 Vf
450 mA
Gesamteinsätze 10.2 W
SK2
System 67 lm/W ²
Einsatz 78 lm/W ²

mit Rand
Länge 122 mm
Breite 60 mm
Höhe 50 mm
0.22 kg

Durchmesser 56 mm
Länge 114 mm
Breite 114 mm
min. Deckenstärke 2 mm
max. Deckenstärke 25 mm
Einbautiefe 120 mm



SASSO 40 round downlight

trim 2 lamps

048-2800614M 048-2898318 002-90753



Projekt / Typ

Notizen

Anzahl / Datum

Montage- anleitung



Beleuchtungs- rechner

