



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Track
 tilt max 310°
 rotation 360°
 white , RAL9016 ¹
 IP20
 754²-1280³ lm

LED

4000 K
 CRI ≥ 95
 L90 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 98 , R_f: 91 , R₍₁₋₁₅₎: 95
 MR 0.85
 MDER 0.77

Optical

focus
 beam angle 17°²-47°³
 PstLM ≤ 1.0 ⁴
 SVM ≤ 0.4 ⁴

Electrical



DIM POTI
 system 23.0 W
 PC1 220-240V
 system 33²-56³ lm/W⁵
 inset 39²-65³ lm/W⁶

Physical


diameter 70 mm
 height 106 mm
 0.9 kg
 tool-free fixation

Track light made of die-cast aluminium; surface white powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 95; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality plano-convex glass lens; precise object focusing through adjustable lens; adjustable beam angle of 17° - 47°; focusing by means of rubberised adjusting ring on the spotlight head; degree of protection IP20; PC1 220-240V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation without tools by means of knurled screw; incl. converter, dimmable with integrated potentiometer; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² beam angle min ³ beam angle max
⁴ Value of containing product at full load (undimmed)
⁵ incl. optical losses and the efficiency of the operating device (converter)
⁶ incl. optical losses

focus 47°

h (m)	E0° (lx)	ø (m)
1	2210	0.87
2	550	1.74
3	250	2.60
4	140	3.47
5	90	4.34

focus 17°

h (m)	E0° (lx)	ø (m)
1	5380	0.30
2	1350	0.60
3	600	0.89
4	340	1.19
5	220	1.49

Installation instructions



Lighting calculator





Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	31
B13	40
B16	50
B20	62
B25	78
C10	52
C13	67
C16	85
C20	104
C25	130

Mounting accessories

RECESSED HOUSING

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
point outlet	traffic white	151	186-072277
point outlet	jet black	151	186-072278



SURFACE HOUSING

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
point outlet	traffic white	120	186-072287
point outlet	jet black	120	186-072288



Optical accessories

SNOOT

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	62	080-5900008



HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	61	080-5900018

