



Project / Type

Notes

Count / Date



| |
|-------------------------------|
| General |
| Ceiling , Track |
| tilt max 310° |
| rotation 360° |
| white , RAL 9016 ¹ |
| IP20 |
| 1400 lm |

| |
|---|
| LED |
| 3000 K |
| CRI ≥ 95 |
| L90 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _f : 94 , R _{t(1-15)} : 96 |
| MR 0.66 |
| MDER 0.6 |


| |
|--------------------------|
| Optical |
| medium |
| beam angle 24° |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Track light made of die-cast aluminium; surface white powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 95; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 24° beam; installed and exchanged without tools; optical attachments available as accessories; degree of protection IP20; PC1; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation without tools by means of knurled screw; incl. converter, dimmable with integrated potentiometer; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

| |
|-----------------------------|
| Electrical |
| DIM POTI |
| 220-240 V |
| system 22.9 W |
| system 61 lm/W ³ |
| PC1 |

| |
|--------------------|
| Physical |
| diameter 70 mm |
| height 98 mm |
| 0.9 kg |
| tool-free fixation |


Light distribution



medium 24°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 5870 | 0.42 |
| 2 | 1470 | 0.84 |
| 3 | 650 | 1.27 |
| 4 | 370 | 1.69 |
| 5 | 230 | 2.11 |

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions



Lighting calculator

