

PABLO tunable white

180-5610D37M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track _____

tilt max 310° _____

rotation 360° _____

white , RAL 9016 ¹ _____

IP20 _____

1140 lm _____

LED

tunable white _____

2700 K - 5000 K _____

CRI ≥ 98 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 97 , R₍₁₋₁₅₎: 98 _____

MR 1.02 _____

MDER 0.93 _____

Optical

medium _____

beam angle 20° _____

Electrical

DALI-2 DT8 _____

220-240 V _____

system 26.6 W _____

system 43 lm/W² _____

PC1 _____

2 DALI Addr. _____

Physical

diameter 70 mm _____


height 98 mm _____

0.95 kg _____

set screw (tool required) _____

Track light made of die-cast aluminium; surface white powder coated; 360° rotatable and 310° tiltable; converter installed in aluminium spotlight housing; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 98; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 20° beam; installed and exchanged without tools; optical attachments available as accessories; degree of protection IP20; PC1; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter fixation by means of set screw; incl. DALI-2 / DT8 converter; point outlet, either in surface mounted housing or recessed housing, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



medium 20°

h (m)	E0° (lx)	ø (m)
1	5890	0.36
2	1470	0.72
3	650	1.07
4	370	1.43
5	240	1.79

Product drawing



¹ RAL code
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

