

L2

MOVE IT 45

090-9L2D3WBB01



Project / Type

Notes

Count / Date



General

Ceiling , Track
black , RAL 9005 ¹
Reflector black
IP20
246 lm
optical inset 57 lm/W²

LED

tunable white
2700 K - 5000 K
CRI \geq 80
L80 / 50000 h
initial MacAdam \leq 3 SDCM
MR 0.55
MDER 0.5

Optical

wallwasher floor
PstLM \leq 1.0 ³
SVM \leq 0.4 ³

Electrical

DALI-2 DT8
48 V
fixture 5.0 W
optical inset 4.3 W
PC3
1 DALI Addr.

Physical


length 81 mm
width 43 mm
height 48 mm
0.2 kg

¹ RAL code

² OPTICAL INSET: incl. consideration of optical losses

³ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



Lighting calculator



[*090-9L2D3WBB01*] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

08.04.2025