

# L2

MOVE IT 45

090-9L2D3WB001



Project / Type

Notes

Count / Date



## General

Ceiling , Track

black , RAL9005 <sup>1</sup>

Reflector chrome

IP20

246 lm

## LED

tunable white

2700 K - 5000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.55

MDER 0.5

## Optical

wallwasher floor

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2 DT8

system 5.0 W

PC3 48V

system 49 lm/W<sup>3</sup>

1 DALI Addr.

## Physical

length 81 mm

width 43 mm

height 48 mm

0.2 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

<sup>3</sup> incl. optical losses and the efficiency of the operating device (converter)


## Installation instructions



## Lighting calculator



## Light distribution



## Product drawing



['090-9L2D3WB001'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.12.2024