



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_




Linear light inset made of aluminium; surface white powder coated; for VITA system module; lighting module with specially computed, asymmetrical high gloss reflector, linear prismatic cover incl. foil; designed for use as indirect light component; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; energy efficient LEDs with high CRI; degree of protection IP20; PC1; with 2 plug-in terminals for through wiring; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Surface \_\_\_\_\_

white , RAL 9010 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

6910 lm \_\_\_\_\_

LED

4000 K \_\_\_\_\_

CRI  $\geq 97$  \_\_\_\_\_

initial MacAdam  $\leq 3$  SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 96 , R<sub>f(1-5)</sub>: 98 \_\_\_\_\_

MR 0.86 \_\_\_\_\_

MDER 0.78 \_\_\_\_\_

Optical

Linear Prismatic \_\_\_\_\_

asymmetric \_\_\_\_\_

PstLM  $\leq 1.0$  <sup>2</sup> \_\_\_\_\_

SVM  $\leq 0.4$  <sup>2</sup> \_\_\_\_\_

Electrical

DALI-2 \_\_\_\_\_

220-240 V \_\_\_\_\_

system 78 W \_\_\_\_\_

system 89 lm/W<sup>3</sup> \_\_\_\_\_

PC1 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

Physical

length 1206 mm \_\_\_\_\_

width 45 mm \_\_\_\_\_

height 22 mm \_\_\_\_\_

3 kg \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

Installation instructions





Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	12
B13	16
B16	20
B20	25
C10	20
C13	27
C16	34
C20	41

Mounting accessories

INDIRECT MODULE

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1007-75-25	099-9911616
	anodised aluminium	1207-75-25	099-9911716
custom cut on building site	anodised aluminium	3621-75-25	099-9911816
custom cut	anodised aluminium		E87210....6



DIRECT / INDIRECT MODULE

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
custom cut	anodised aluminium		E87220....6
	anodised aluminium	1007-130-25	099-9912616
	anodised aluminium	1207-130-25	099-9912716
custom cut on building site	anodised aluminium	3621-130-25	099-9912816



Mounting accessories

STANDARD RAIL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1007-130-29	099-9951616
	anodised aluminium	1207-130-29	099-9951716
	anodised aluminium	3621-130-29	099-9951816
custom cut	anodised aluminium		E87280....6



MOUNTING CHANNEL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1210-120-43	099-9921716
	anodised aluminium	3630-120-43	099-9921816
	anodised aluminium	1010-120-43	099-9921616
custom cut	anodised aluminium		E87240....6





## Mounting accessories

### END CAP

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
left for indirect module	anodised aluminium	75-25-3	099-9911016
right for indirect module	anodised aluminium	75-25-3	099-9911116
left for direct / indirect module	anodised aluminium	130-25-3	099-9912016
right for direct / indirect module	anodised aluminium	130-25-3	099-9912116
left for standard rail	anodised aluminium		099-9951016
right for standard rail	anodised aluminium		099-9951116



### END CAPS

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
1 pair   for mounting channel 50 mm	anodised aluminium	120-50-3	099-9931016
1 pair   for mounting channel 55 mm	anodised aluminium	120-50-3	099-9932016
1 pair   for mounting channel 75 mm	anodised aluminium	120-50-3	099-9933016



## Mounting accessories

### LINEAR CONNECTOR SET

TYPE	COLOUR	ARTICLE NUMBER(S)
for mounting channel	anodised aluminium	099-9941116
for direct / indirect module	anodised aluminium	099-9942116
for indirect module	anodised aluminium	099-9943116
for D/I module to I channel L	anodised aluminium	099-9944116
for D/I module to I channel R	anodised aluminium	099-9945116



## Electrical accessories

### THROUGH WIRE

TYPE	ARTICLE NUMBER(S)
4×1,5mm <sup>2</sup> + 1×2,5mm <sup>2</sup>   10 pieces	099-9940110



## Electrical accessories

### DALI MODULE

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
for control of 4 scenes / 2 groups	48-28-15	002-54026





## Electrical accessories

### MASTER UNIT

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
single patient room	85-48-160	099-2291137
double patient room	85-48-160	099-2291237



### INSTALLATION HOUSING

L-W-H (MM)	ARTICLE NUMBER(S)
71-75-135	099-2290000



### SAFETY FRAME FOR MASTER UNIT

L-W-H (MM)	ARTICLE NUMBER(S)
108-15-182	099-2298007



## Electrical accessories

### DALI LIGHT SENSOR

TYPE	Ø (MM)	ARTICLE NUMBER(S)
recessed ceiling mounted	86	002-54051
surface mounted	86	002-54058
socket mounted	103	002-54053



## Optical accessories

### BLIND COVER

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1006-45-22	099-9913616
	anodised aluminium	1206-45-22	099-9913716
custom cut on building site	anodised aluminium	3620-45-22	099-9913816
custom cut	anodised aluminium		E87230...6



### COVER SMALL

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1009-120-50	099-9931616
	anodised aluminium	1209-120-50	099-9931716
	anodised aluminium	3629-120-50	099-9931816
custom cut	anodised aluminium		E87250...6



### COVER MEDIUM

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1009-120-55	099-9932616
	anodised aluminium	1209-120-55	099-9932716
	anodised aluminium	3629-120-55	099-9932816
custom cut	anodised aluminium		E87260...6



### COVER BIG

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
	anodised aluminium	1009-120-75	099-9933616
	anodised aluminium	1209-120-75	099-9933716
	anodised aluminium	3629-120-75	099-9933816
custom cut	anodised aluminium		E87270...6

