

# L4

MOVE IT 45

090-9L4D3FB001



Project / Type

Notes

Count / Date



## General

Ceiling , Track

black , RAL 9005 <sup>1</sup>

Reflector chrome

IP20

746 lm

optical inset 87 lm/W<sup>2</sup>

## LED

tunable white

2700 K - 5000 K

CRI ≥ 80

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.55

MDER 0.5

## Optical

flood square

beam angle 52°

UGR < 16 , ≥65° <1500 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2 DT8

48 V

fixture 10:1 W

fixture 74 lm/W<sup>4</sup>

optical inset 8.6 W

PC3

1 DALI Addr.

## Physical

length 156 mm

width 43 mm

height 48 mm

0.4 kg


<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses


<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

