

# L4

MOVE IT 45

090-9L463WB001



Project / Type

Notes

Count / Date



## General

Ceiling , Track

black , RAL 9005 <sup>1</sup>

Reflector chrome

IP20

1310 lm

optical inset 114 lm/W<sup>2</sup>

## LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 102 , R<sub>f</sub>: 93 , R<sub>f(-15)</sub>: 92

MR 0.81

MDER 0.74

## Optical

wallwasher floor

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2

48 V

fixture 13.6 W

fixture 96 lm/W<sup>4</sup>

optical inset 11.5 W

PC3

1 DALI Addr.

## Physical

length 156 mm

width 43 mm

height 48 mm

0.4 kg


<sup>1</sup> RAL code

<sup>2</sup> OPTICAL INSET: incl. consideration of optical losses


<sup>3</sup> Value of containing product at full load (undimmed)

<sup>4</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

