

# UNICO Q9 basic

trim

090-7Q941D0B21 090-7Q9020W



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed

black reflector , RAL 9016 <sup>1</sup>

Mounting set traffic white

IP20

2890 lm

## LED

2700 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 101 , R<sub>f</sub>: 91 , R<sub>t(1-15)</sub>: 89

MR 0.56

MDER 0.51

## Optical

wide flood round

beam angle 72°

$\geq 65^\circ$  <1500 cd/m<sup>2</sup>

## Electrical

non DIM

220-240 V

system 29.9 W

system 97 lm/W<sup>2</sup>

PC2

## Physical

trim

length 138 mm

width 138 mm

height 51 mm

0.71 kg

## Cutout

length 130 mm

width 130 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 90 mm

<sup>1</sup> RAL code

<sup>2</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses  
SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.


## Installation instructions



## Lighting calculator



## Light distribution



## Product drawing

