

UNICO Q1basic

trim

090-7Q163D0021 090-7Q1020W



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| |
|--|
| Ceiling , Recessed |
| chrome reflector , RAL 9016 ¹ |
| Mounting set traffic white |
| IP20 |
| 462 lm |

LED

| |
|--|
| 4000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 102 , R _f : 93 , R _{f(1-15)} : 92 |
| MR 0.81 |
| MDER 0.74 |

Optical

| |
|------------------------------|
| wide flood round |
| beam angle 72° |
| ≥65° <3000 cd/m ² |
| PstLM ≤ 1.0 ² |
| SVM ≤ 0.4 ² |

Electrical

| |
|-----------------------------|
| DALI-2 |
| 220-240 V |
| system 6.0 W |
| system 77 lm/W ³ |
| PC2 |


Physical

| |
|--------------|
| trim |
| length 63 mm |
| width 63 mm |
| height 51 mm |
| 0.2 kg |

Cutout

| |
|------------------------------|
| length 50 mm |
| width 50 mm |
| min. ceiling thickness 2 mm |
| max. ceiling thickness 25 mm |
| recessed depth 150 mm |

Light distribution



Product drawing



Installation instructions



Lighting calculator

