

## UNICO linear

recessed


**EN** Rectangular recessed multi-downlight made of die-cast aluminium; equipped with two (L2) / three (L3) / four (L4) / six (L6) individually selectable or pre-specified, customised light elements; installation without tools in mounting set with ball catch system; easy electrical installation by means of reverse polarity protected plug-in connections; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation possible in different housings; high-quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

**DE** Rechteckiger Einbau-Multi-Downlight aus Aluminiumdruckguss; bestückt mit zwei (L2) / drei (L3) / vier (L4) / sechs (L6) individuell wählbaren oder fix definierten, anwendungsspezifischen Optiken; werkzeuglose Montage im Montageset durch Kugelschnappsystem; einfache elektrische Montage durch verpolungssichere Steckverbindung; geeignet für Deckenstärken von 2-25 mm; Oberfläche pulverbeschichtet; Einbau in unterschiedlichen Gehäusen möglich; hochwertiger Reflektor mit mikrofaccettierter, aluminiumbedampfter Oberfläche; präzise Abstrahlcharakteristik mit unterschiedlichen symmetrischen Lichtverteilungen; oder mit asymmetrischer Lichtverteilung; energieeffiziente High-Power-LEDs mit sehr guter Farbwiedergabe; klirrfrei

### Quickinfo

2700 K, 3000 K, 4000 K  
 CRI ≥ 90, 3 SDCM  
 UGR ≤ 19 / 65° ≤ 1500 cd/m²  
 L2 up to 104 lm/W  
 L3 up to 111 lm/W  
 L4 up to 116 lm/W  
 L6 up to 117 lm/W  
 L90 @ 50 000 h  
 non DIM, DALI-2


### Types




### Colours



### Light optics



DiiA® standards  
 251, 252, 253



one luminaire  
 multiple scenes



plug / socket  
 connector



black & gold  
 reflector



tunable white  
 2700-5000K

### Order options

<b>COLOUR TEMPERATURE</b>	☑☑
2700K	4
3000K	5
4000K	6

<b>CONTROL</b>	⬇
non DIM	1
DALI-2	3

<b>LIGHT OPTIC</b>	▲
spot round (UGR≤10)	K
narrow medium round (UGR≤10)	N
medium round (UGR≤10)	B
medium square (UGR≤10)	E
flood round (UGR≤16)	C
flood square (UGR≤19)	F
wide flood round	D
wide flood square	G

<b>MATERIAL COLOUR</b>	☑
○ traffic white RAL 9016	W
● jet black RAL 9005	B

<b>LIGHT OPTIC COLOUR</b>	■
chrome reflector	0
black reflector*	B

\*not available for spot round, narrow medium round and wallwasher

### Options on request

<b>COLOUR TEMPERATURE</b>
tunable white 2700–5000K
DALI-2 DT8

<b>LIGHT OPTIC COLOUR</b>
gold reflector


<b>MOUNTING SET</b>
acoustic soft ceilings

### Product configurator




Create your own UNICO PRO  
[unico.xal.com](http://unico.xal.com)

### Planning information



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

### UNICO L2 basic recessed




<b>FLOOR</b>			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
7.3 W	up to 762 lm	090-7L2:::▲0■21	
choose one light optic ▲ from the options on the left depending on your room needs			

<b>WALL</b>			
2x wallwasher			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
7.3 W	645 lm	090-7L2:::▲A0022	

<b>CORRIDOR</b>			
2x rectangular			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
7.3 W	643 lm	090-7L2:::▲R0■21	

<b>WALL + FLOOR</b>			
2x wallwasher floor			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
7.3 W	672 lm	090-7L2:::▲W0■22	

### UNICO L3 basic recessed




<b>FLOOR</b>			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
9.8 W	up to 1090 lm	090-7L3:::▲0■21	
choose one light optic ▲ from the options on the left depending on your room needs			


<b>WALL</b>			
3x wallwasher			
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>	
9.8 W	924 lm	090-7L3:::▲A0021	

### Accessories


<b>MOUNTING SET WITH TRIM</b>			
for intermediate ceilings 2–25 mm			
<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>CUTOUT (mm)</b>	<b>ORDER CODE</b>
L2	101-63-30	90-50	090-7L2020
L3	138-63-30	130-50	090-7L3020



<b>TRIMLESS MOUNTING SET</b>			
for installation in plasterboard ceilings 12.5/15/20/25 mm			
<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>CUTOUT (mm)</b>	<b>ORDER CODE</b>
L2	88-50-47	90-50	090-7L20100
L3	125-50-47	130-50	090-7L30100



<b>THROUGH WIRING CONNECTION BOX</b>			
<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>ORDER CODE</b>	
non DIM cable ø4–12 mm	105-58-30	005-2531110	
DALI cable ø4–12 mm	105-58-30	005-2551110	



**LUMINOUS FLUX** value calculated for  
 3000K, CRI≥90, colour white, reflector chrome  
 2700K -6%, 4000K +7%

**Order options**

**COLOUR TEMPERATURE** ◆◆

2700K	4
3000K	5
4000K	6

**CONTROL** ◆

non DIM	1
DALI-2	3

**LIGHT OPTIC** ▲

spot round (UGR≤10)	K
narrow medium round (UGR≤10)	N
medium round (UGR≤10)	B
medium square (UGR≤10)	E
flood round (UGR≤16)	C
flood square (UGR≤19)	F
wide flood round	D
wide flood square	G

**MATERIAL COLOUR** ▣

○ traffic white RAL 9016	W
● jet black RAL 9005	B

**LIGHT OPTIC COLOUR** ■

chrome reflector	0
black reflector*	B

\*not available for spot round, narrow medium round and wallwasher

**Options on request**

**COLOUR TEMPERATURE**

tunable white 2700–5000K
DALI-2 DT8


**LIGHT OPTIC COLOUR**

gold reflector
----------------

**MOUNTING SET**

acoustic soft ceilings
------------------------

**Product configurator**




Create your own UNICO PRO  
[unico.xal.com](http://unico.xal.com)

**Planning information**



The icons of the light optics are shown in the reflected ceiling plan (RCP) view.

**UNICO L4 basic recessed**



**FLOOR**

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	up to 1520lm	090-7L4 <span style="color: blue;">◆◆▲■</span> 21

choose one light optic ▲ from the options on the left depending on your room needs



**WALL**

4x wallwasher

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1290lm	090-7L4 <span style="color: blue;">◆◆▲</span> 021



**WALL + FLOOR**


4x wallwasher floor

SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
13.1W	1340lm	090-7L4 <span style="color: blue;">◆◆▲</span> W0 <span style="color: blue;">■</span> 22

**Accessories**

**MOUNTING SET WITH TRIM**


for intermediate ceilings 2–25mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	176-63-30	165-50	090-7L4020 <span style="color: blue;">▣</span>


**TRIMLESS MOUNTING SET**

for installation in plasterboard ceilings 12.5/15/20/25mm



TYPE	L-W-H (mm)	CUTOUT (mm)	ORDER CODE
L4	163-50-47	165-50	090-7L40100

**THROUGH WIRING CONNECTION BOX**



TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø4–12mm	105-58-30	005-2531110
DALI cable ø4–12mm	105-58-30	005-2551110

**LUMINOUS FLUX** value calculated for  
 3000K, CRI ≥ 90, colour white, reflector chrome  
 2700K -6%, 4000K +7%

## Order options

### COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

### CONTROL

non DIM	1
DALI-2	3

### LIGHT OPTIC

spot round (UGR $\leq$ 10)	K
narrow medium round (UGR $\leq$ 10)	N
medium round (UGR $\leq$ 10)	B
medium square (UGR $\leq$ 10)	E
flood round (UGR $\leq$ 16)	C
flood square (UGR $\leq$ 19)	F
wide flood round	D
wide flood square	G

### MATERIAL COLOUR

<input type="radio"/> traffic white RAL 9016	W
<input checked="" type="radio"/> jet black RAL 9005	B

### LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

\*not available for spot round, narrow medium round and wallwasher

## Options on request

### COLOUR TEMPERATURE

tunable white 2700–5000K





DALI-2 DT8

### LIGHT OPTIC COLOUR

gold reflector

### MOUNTING SET

acoustic soft ceilings



## UNICO L6 basic recessed



### FLOOR

<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
18.6 W	up to 2180lm	090-7L6:::▲0■21

choose one light optic ▲ from the options on the left depending on your room needs

### WALL

6x wallwasher		
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
18.6 W	1850lm	090-7L6:::▲A0021

### CORRIDOR

6x rectangular		
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
18.6 W	1840lm	090-7L6:::▲R0■21

### WALL + FLOOR

6x wallwasher floor		
<b>SYSTEM POWER</b>	<b>LUMINOUS FLUX</b>	<b>ORDER CODE</b>
18.6 W	1930lm	090-7L6:::▲W0■21

## Accessories

### MOUNTING SET WITH TRIM

for intermediate ceilings 2–25 mm

<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>CUTOUT (mm)</b>	<b>ORDER CODE</b>
L6	251-63-30	240-50	090-7L6020■

### TRIMLESS MOUNTING SET

for installation in plasterboard ceilings 12.5/15/20/25 mm

<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>CUTOUT (mm)</b>	<b>ORDER CODE</b>
L6	238-50-47	240-50	090-7L60100

### THROUGH WIRING CONNECTION BOX

<b>TYPE</b>	<b>L-W-H (mm)</b>	<b>ORDER CODE</b>
non DIM cable $\varnothing$ 4–12 mm	105-58-30	005-2531110
DALI cable $\varnothing$ 4–12 mm	105-58-30	005-2551110

**LUMINOUS FLUX** value calculated for  
3000K, CRI $\geq$ 90, colour white, reflector chrome  
2700K -6%, 4000K +7%