

# UNICO wall 1 lamp

trim

090-6L163UB001 090-7L2020B



Project / Type
Notes
Count / Date



## General

Wall , Recessed
black , RAL 9005 <sup>1</sup>
jet black
IP20
562 lm

## LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 102 , R <sub>f</sub> : 93 , R <sub>f(1-5)</sub> : 92
MR 0.81
MDER 0.74

## Optical

asymmetric
beam angle 148°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2
220-240 V
system 9.9 W
system 57 lm/W <sup>3</sup>
PC2


## Physical

trim
length 43 mm
width 53 mm
height 80 mm
0.06 kg

## Cutout

length 90 mm
width 50 mm
recessed depth 150 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

## Installation instructions

