

# UNICO wall 1 lamp

trim



090-6L161UB001 090-7L2020B



Project / Type

Notes

Count / Date



## General

Wall , Recessed

black , RAL9005 <sup>1</sup>

jet black

IP20

562 lm

## LED

4000 K

CRI  $\geq$  90

L90 / 50000 h

initial MacAdam  $\leq$  3 SDCM

R<sub>g</sub>: 102 , R<sub>f</sub>: 93 , R<sub>f(1-15)</sub>: 92

MR 0.81

MDER 0.74

## Optical

wide floor

beam angle 148°

PstLM  $\leq$  1.0 <sup>2</sup>

SVM  $\leq$  0.4 <sup>2</sup>

## Electrical

non DIM

9.9 W

PC2

57 lm/W

## Physical

trim

length 43 mm

width 53 mm

height 80 mm

0.32 kg

## Cutout

length 90 mm

width 50 mm


recessed depth 95 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Light distribution



## Product drawing



[090-6L161UB001 090-7L2020B] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

03.07.2024

1 / 1