

# UNICO wall 1 lamp

trim



090-6L143UB001 090-7L2020W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Wall , Recessed \_\_\_\_\_

black , RAL9005 <sup>1</sup> \_\_\_\_\_

traffic white \_\_\_\_\_

IP20 \_\_\_\_\_

492 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI  $\geq$  90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq$  3 SDCM \_\_\_\_\_

R<sub>g</sub>: 101 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.56 \_\_\_\_\_

MDER 0.51 \_\_\_\_\_

## Optical

wide floor \_\_\_\_\_

beam angle 148° \_\_\_\_\_

PstLM  $\leq$  1.0 <sup>2</sup> \_\_\_\_\_

SVM  $\leq$  0.4 <sup>2</sup> \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

9.9 W \_\_\_\_\_

PC2 \_\_\_\_\_

50 lm/W \_\_\_\_\_

## Physical

trim \_\_\_\_\_

length 43 mm \_\_\_\_\_

width 53 mm \_\_\_\_\_

height 80 mm \_\_\_\_\_

0.41 kg \_\_\_\_\_

## Cutout

length 90 mm \_\_\_\_\_

width 50 mm \_\_\_\_\_


recessed depth 150 mm \_\_\_\_\_

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Light distribution



## Product drawing



[090-6L143UB001 090-7L2020W] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

22.07.2024

1 / 1