

# UNICO L6 basic

ceiling

090-1L651KG001



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



### General

|                              |  |
|------------------------------|--|
| Ceiling , Surface            |  |
| grey , RAL 9006 <sup>1</sup> |  |
| Reflector chrome             |  |
| IP20                         |  |
| 1710 lm                      |  |

### LED

|  |  |
|--|--|
| 3000 K   |  |
| CRI ≥ 90   |  |
| L90 / 50000 h  |  |
| initial MacAdam ≤ 3 SDCM   |  |
| R <sub>g</sub> : 100 , R <sub>f</sub> : 92 , R <sub>f(1-15)</sub> : 91 |  |
| MR 0.64  |  |
| MDER 0.58  |  |

### Optical

|   |  |
|---|--|
| spot round                              |  |
| beam angle 15°                          |  |
| UGR ≤ 10 , ≥65° <1500 cd/m <sup>2</sup> |  |
| PstLM ≤ 1.0 <sup>2</sup>                |  |
| SVM ≤ 0.4 <sup>2</sup>                  |  |


### Electrical

|                             |  |
|-----------------------------|--|
| non DIM                     |  |
| 220-240 V                   |  |
| system 27.1 W               |  |
| system 63 lm/W <sup>3</sup> |  |
| PC1                         |  |


### Physical

|               |  |
|---------------|--|
| length 239 mm |  |
| width 51 mm   |  |
| height 90 mm  |  |
| 0.7 kg        |  |

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

