

UNICO Q4basic

ceiling

090-1Q441KB001



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|-------------------------------|--|
| Ceiling , Surface | |
| black , RAL 9005 ¹ | |
| Reflector chrome | |
| IP20 | |
| 1100 lm | |

LED

| | |
|--|--|
| 2700 K | |
| CRI ≥ 90 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 101 , R _f : 91 , R _{t(1-15)} : 89 | |
| MR 0.56 | |
| MDER 0.51 | |

Optical

| | |
|---|--|
| spot round | |
| beam angle 15° | |
| UGR ≤ 10 , ≥65° <1500 cd/m ² | |
| PstLM ≤ 1.0 ² | |
| SVM ≤ 0.4 ² | |


Electrical

| | |
|-----------------------------|--|
| non DIM | |
| 220-240 V | |
| system 19.3 W | |
| system 57 lm/W ³ | |
| PC1 | |


Physical

| | |
|--------------|--|
| length 88 mm | |
| width 88 mm | |
| height 90 mm | |
| 0.5 kg | |

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

