

# UNICO L4basic

ceiling

090-1L461GB001



Project / Type
Notes
Count / Date



### General

Ceiling , Surface
black , RAL 9005 <sup>1</sup>
Reflector chrome
IP20
2060 lm

### LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 102 , R <sub>f</sub> : 93 , R <sub>f(1-15)</sub> : 92
MR 0.81
MDER 0.74

### Optical

wide flood square
beam angle 71°
≥65° <3000 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>


### Electrical

non DIM
220-240 V
system 19.3 W
system 107 lm/W <sup>3</sup>
PC1

### Physical

length 164 mm
width 51 mm
height 90 mm
0.55 kg

### Light distribution



### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> FIXTURE: incl. consideration of optical losses & internal control unit losses SYSTEM: incl. consideration of optical losses, internal control unit losses & operating device efficiency.

### Installation instructions



### Lighting calculator

